

RT-TV-3M-290

3x telezentrisches Objektiv für Detektorgrößen bis zu 1/2" mit sehr großem Arbeitsabstand

ZUSATZANGABEN

Vergößerung		3.00
Bildkreis Ø	(mm)	8.0
Max detector size		1/2"

Bildbereich des Objekts

mit 1/3"-Detektor (4.8 x 3.6 mm)	(mm x mm)	1.6 x 1.2
mit 1/2.5"-Detektor (5.70 x 4.28 mm)	(mm x mm)	1.9 x 1.4
mit 1/2"-Detektor (6.4 x 4.8 mm)	(mm x mm)	2.1 x 1.6
mit 1/1.8"-Detektor (7.13 x 5.37 mm)	(mm x mm)	-

Optische Angaben

Arbeitsabstand	(mm)	290.70
F/#		43.0
Distortion	(%)	0.10
Field depth	(mm)	0.41
Nominal resolving power	(µm)	9.60

Mechanische Angaben

Mount		C
Länge	(mm)	216.5
Durchmesser	(mm)	27.0
Gewicht	(g)	215



HINWEISE

1. F/# = F-number, wF/# = working F-number: die reale Blendenzahl eines als Makro verwendeten Objektivs.

KOMPATIBLE PRODUKTE

LTDMC-Serie LED-Dom-Dauerleuchten

RT-IDS4-00-150-2-W-24V-FL	Continuous LED dome, 185 mm outer diameter, white
RT-IDS4-00-150-2-R-24V-FL	Continuous LED dome, 185 mm outer diameter, red
RT-IDS4-00-150-2-G-24V-FL	Continuous LED dome, 185 mm outer diameter, green
RT-IDS4-00-150-2-B-24V-FL	Continuous LED dome, 185 mm outer diameter, blue

LTLAIC-Serie Diffuse LED-Dauer-Flachwinkel-Ringleuchten

RT-DLR2-60-050-2-W-24V-FL	Continuous LED low angle diffused ringlight, inner diameter 18 mm, 60°, white
RT-DLR2-60-050-2-R-24V-FL	Continuous LED low angle diffused ringlight, inner diameter 18 mm, 60°, red
RT-DLR2-60-050-2-G-24V-FL	Continuous LED low angle diffused ringlight, inner diameter 18 mm, 60°, green
RT-DLR2-60-050-2-B-24V-FL	Continuous LED low angle diffused ringlight, inner diameter 18 mm, 60°, blue

LTLADC-Serie Direkte LED-Dauer-Flachwinkel-Ringleuchten

RT-LLA-75-130-3-W-24V-FL	Continuous LED low angle direct ringlights, inner diameter 94 mm, 75°, white
RT-LLA-75-130-3-R-24V-FL	Continuous LED low angle direct ringlights, inner diameter 94 mm, 75°, red
RT-LLA-75-130-3-G-24V-FL	Continuous LED low angle direct ringlights, inner diameter 94 mm, 75°, green
RT-LLA-75-130-3-B-24V-FL	Continuous LED low angle direct ringlights, inner diameter 94 mm, 75°, blue

LTRNDC-Serie
Direkte LED-Dauer-Ringleuchten

RT-LSW-15-050-2-W-24V-FL	Continuous LED direct ringlight, inner diameter 28 mm, 15°, white
RT-LSW-15-050-2-R-24V-FL	Continuous LED direct ringlight, inner diameter 28 mm, 15°, red
RT-LSW-15-050-2-G-24V-FL	Continuous LED direct ringlight, inner diameter 28 mm, 15°, green
RT-LSW-15-050-2-B-24V-FL	Continuous LED direct ringlight, inner diameter 28 mm, 15°, blue
RT-LSW-45-070-3-W-24V-FL	Continuous LED direct ringlight, inner diameter 35 mm, 45°, white
RT-LSW-45-070-3-R-24V-FL	Continuous LED direct ringlight, inner diameter 35 mm, 45°, red
RT-LSW-45-070-3-G-24V-FL	Continuous LED direct ringlight, inner diameter 35 mm, 45°, green
RT-LSW-45-070-3-B-24V-FL	Continuous LED direct ringlight, inner diameter 35 mm, 45°, blue

LTBFC-Serie
Flache, seitlich abstrahlende LED-Dauer-Hintergrundleuchten

RT-BHDS-25X36-1-W-24V-FL	Continuous flat side-emitting LED backlight, one side edge to edge type, 36X25 illumination area, white
RT-BHDS-25X36-1-R-24V-FL	Continuous flat side-emitting LED backlight, one side edge to edge type, 36X25 illumination area, red
RT-BHDS-25X36-1-G-24V-FL	Continuous flat side-emitting LED backlight, one side edge to edge type, 36X25 illumination area, green
RT-BHDS-25X36-1-B-24V-FL	Continuous flat side-emitting LED backlight, one side edge to edge type, 36X25 illumination area, blue

LTBRDC-Serie
LED-Dauer-Balkenleuchten

RT-LBRX-00-040-6-W-24V-FL	Continuous LED bar light, 40X26.3 illumination area, white
RT-LBRX-00-040-6-R-24V-FL	Continuous LED bar light, 40X26.3 illumination area, red
RT-LBRX-00-040-6-G-24V-FL	Continuous LED bar light, 40X26.3 illumination area, green
RT-LBRX-00-040-6-B-24V-FL	Continuous LED bar light, 40X26.3 illumination area, blue

LTCXC-Serie
LED-Dauer-Koaxialeuchten

RT-CAS2-00-025-X-W-24V-FL	Continuous LED coaxial light, 27x27 active area, white
RT-CAS2-00-025-X-R-24V-FL	Continuous LED coaxial light, 27x27 active area, red
RT-CAS2-00-025-X-G-24V-FL	Continuous LED coaxial light, 27x27 active area, green
RT-CAS2-00-025-X-B-24V-FL	Continuous LED coaxial light, 27x27 active area, blue